

○ Specifications

	RV-5030A
Tunnel size	500 (W) X 300 (H) mm
Tunnel Width	400mm
Belt speed	0.2m/sec
Belt direction	Right to left
Inspectable sample size	440 (W) X 800 (D) X 280 (H) mm
Maximum weight	10kg
Tube voltag	80kV
Tube current	0.5mA
X-ray penetration power	8mm : Fe
Line sensor	Single L-shaped sensor
OS	Windows XP
Software	RV System Viewer
Hard disk	200GB
Display	22" LCD Monitors (2)
Size	1430 (W) X 903 (D) X 1200 (H) mm (excluding monitor)
System weight (excluding monitor)	405kg
Power supply	Single-phase AC 220V±10% 50/60 Hz
Power consumption	1.2kVA
Ambient noise	Below 65dB
X-ray leakage	Below 1μSv/h
Operating temperature	5~35°C
Operating humidity	20 ~ 80%RH (no condensation)
Standard accessories	Color ink-jet printer, DVD, CD, Input/output table, Label printer

○ Standard Accessories

Label printer




Includes two label rolls
55x12mm, 735 labels/roll

Input/output table



○ Dimensions



The specifications are valid outside Japan.
Specifications subject to change without notice.



Rigaku Corporation

3-9-12, Matsubara-cho, Akishima-shi,
Tokyo 196-8666, Japan
Phone:+81-42-545-8167 Fax:+81-42-545-3226



NEW **RV-5030A**

Foreign Object X-ray Inspection Instrument



Dual-screens provide drastically improved inspection accuracy!

Foreign Object X-ray Inspection Instrument
RV-5030A




Inspect a wide variety of goods with a single instrument ... shoes, bags, clothes and more!

Dual-screen Display

Don't miss anything. The dual-screen display lets you see each part of the item you are inspecting with unparalleled clarity and contrast.

* It is also possible to have both screens set to display the same image.




High-energy X-rays

Higher-energy X-rays enable a broad range of inspection targets (80kv)
Can be used for the inspection of thick metals, shoe soles etc.

Two-person Team Inspection

Two inspectors simultaneously judging results means that you can expect a dramatic improvement inspection accuracy.




JUDGMENT
OK / NG Buttons

Easy-to-use Control Panel

Control panel at your fingertips provides easy-to-use, push-button operation.




Control panel



RV System Viewer screenshot

Enlarged in-tunnel inspection area


L-shaped line sensor lets you see every area in the tunnel. No blind spots.



Increased Tunnel Size

Dramatically increased tunnel size (500x300mm) makes it possible to inspect bags and other general merchandise.

Compared to a previous instrument (EV-60S)



Additional Features

Inspection management track and compare total

Report creation generate reports with customizable names, colors etc.

Serial inspection mode examine 5,000 pairs of low shoes in 8 hours

Autozoom zoom in with just one button

Plenty of space to save results save up to 2,000,000 inspection images

